


# CONTINUOUS FLEX CABLES

also available  
with color code  
acc. to US 3

## SD 980 CP TP High speed continuous flex shielded twisted pairs heavy duty halogen free polyurethane control cable



21198 80°C 300V CSA AWM I/II A/B 80°C 300V FT1 FT2 CE

Marking for SD 980 CP TP 77890725: SAB BRÖCKSKES · D-VIERSEN · 77890725 7 x 2 x 0,25 mm<sup>2</sup> SD 980 CP TP 24 AWG/7pr 77892407  
AWM Style 21198 80°C 300V CSA AWM I/II A/B 80°C 300V FT1 FT2 CE

SD 980 CP TP is a continuous flex shielded multi-conductor 80°C, 300 V cable designed specifically for the most stressful ultra high speed applications requiring a very small bending radius. The unique design allows this cable to excel in applications where ordinary flexing cables fail. The halogen free polyurethane jacket cable with colored conductors passes the stringent VDE test 0282 part 10 and HD 22.10 oil test and provides excellent resistance to chemicals and abrasion. An overall tinned copper shield is recommended whenever electrical interference distorts signal transmission, or when EMI emissions need to be suppressed.

B  
33

### Construction:

<b>Conductor:</b>	bare copper strands, extra fine wires
<b>Insulation:</b>	TPE
<b>Color code:</b>	with reference to DIN 47100
<b>Stranding:</b>	conductors twisted to pairs, pairs twisted in specially adjusted layering with netting tape over each layer
<b>Screen:</b>	tinned copper braiding
<b>Wrapping:</b>	non-woven tape
<b>Jacket material:</b>	TMPU acc. to DIN VDE 0282 part 10 + HD 22.10 with mat surface
<b>Jacket color:</b>	gray

### Technical data:

<b>Peak operating voltage:</b>	<b>DIN VDE:</b> max. 350 V <b>UL/CSA:</b> 300 V
<b>Testing voltage U:</b>	1500 V acc. to DIN VDE 0472 part 509 conductor/screen 1200V
<b>Min. bending radius continuous flexing:</b>	7.5 x O.D.
<b>Radiation resistance:</b>	5 x 10 <sup>7</sup> cJ/kg
<b>Temperature range static: flexing:</b>	<b>DIN VDE</b> <b>UL/CSA:</b> up to +80°C -50/+90°C -40/+90°C
<b>Zero halogen:</b>	acc. to DIN VDE 0472 part 815 and IEC 60754-1
<b>Burning characteristics:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2, UL VW-1, CSA FT1 and FT2
<b>Oil resistance:</b>	very good - TMPU acc. to DIN VDE 0282 part 10 + HD 22.10
<b>Chem. resistance:</b>	good against acids, alkalines, solvents, hydraulic liquids etc.
<b>Continuous flexibility:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/28

### Outstanding features:

- ▶ **labs uncritical**  
(labs = enamel moisturing interfering substances)
- ▶ **flexible at low temperatures**
- ▶ **halogen-free**
- ▶ **travel > 10 m is possible**
- ▶ **good EMC characteristics**
- ▶ **high abrasion resistance**

item no.	no. of pairs	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft
▶ 26 AWG (≈ 18/38) • 0.14 mm <sup>2</sup>				
77892602	2	0.201	5.1	23
77892603	3	0.220	5.6	26
77892604	4	0.248	6.3	32
77892605	5	0.264	6.7	36
77892607	7	0.283	7.2	43
77892610	10	0.331	8.4	56
77892614	14	0.366	9.3	71
77892618	18	0.406	10.3	91
77892625	25	0.461	11.7	117

item no.	no. of pairs	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft
▶ 24 AWG (≈ 14/34) • 0.25 mm <sup>2</sup>				
77892402	2	0.220	5.6	28
77892403	3	0.244	6.2	35
77892404	4	0.272	6.9	40
77892405	5	0.291	7.4	46
77892407	7	0.311	7.9	57
77892410	10	0.362	9.2	74
77892414	14	0.429	10.9	106
77892418	18	0.457	11.6	126
77892425	25	0.551	14.0	185

item no.	no. of pairs	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft
▶ 22 AWG (≈ 7/30) • 0.34 mm <sup>2</sup>				
77892202	2	0.232	5.9	32
77892203	3	0.256	6.5	40
77892204	4	0.291	7.4	48
77892205	5	0.311	7.9	54
77892207	7	0.335	8.5	66
77892210	10	0.390	9.9	87
77892214	14	0.457	11.6	125
77892218	18	0.492	12.5	150
77892225	25	0.579	14.7	215

Other dimensions and colors are possible on request.

