

CONTINUOUS FLEX CABLES

also available
with blue, red and
white conductors

S 980 CP High speed continuous flex shielded heavy duty halogen free polyurethane control cable



Marking for S 980 CP 77840715: SAB BRÖCKSKES · D-VIERSEN · 77840715 7 x 1,5 mm² S 980 CP 16 AWG/7c 77841607
AWM Style 21060 80°C 600V CSA AWM I/II A/B 80°C 600V FT1 FT2 CE

S 980 CP is a continuous flex shielded multi-conductor 80°C, 600 V cable designed specifically for the most stressful ultra high speed applications requiring a very small bending radius. The unique design allows this cable to excel in applications where ordinary flexing cables fail. The halogen free polyurethane jacket cable with black numbered conductors passes the stringent VDE test 0282 part 10 and HD 22.10 oil test and provides excellent resistance to chemicals and abrasion. An overall tinned copper shield is recommended whenever electrical interference distorts signal transmission, or when EMI emissions need to be suppressed.

B
31

Construction:

Conductor:	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 6
Insulation:	TPE
Color code:	black conductors with consecutive numbers acc. to EN 50334; green-yellow earth wire from 3 conductors
Stranding:	specially adjusted layering with netting tape over each layer
Inner jacket:	special SABIX®
Wrapping:	netting tape
Screen:	tinned copper braiding
Wrapping:	non-woven tape
Jacket material:	TMPU acc. to DIN VDE 0282 part 10 + HD 22.10 with mat surface
Jacket color:	gray

Outstanding features:

- ▶ **labs uncritical**
(labs = enamel moisturing interfering substances)
- ▶ **flexible at low temperatures**
- ▶ **travel > 10 m is possible**
- ▶ **good EMC characteristics**
- ▶ **high abrasion resistance**

Technical data:

Nominal voltage:	DIN VDE: U ₀ /U 300/500 V UL/CSA: 600 V
Testing voltage U:	3000 V acc. to DIN VDE 0281 part 2 + HD 21.2 conductor/screen 2000 V
Min. bending radius continuous flexing:	7.5 x O.D.
Radiation resistance:	5 x 10 ⁷ cJ/kg
Temperature range static:	DIN VDE -50/+90°C UL/CSA: up to +80°C
flexing:	-40/+90°C
Zero halogen:	acc. to DIN VDE 0472 part 815 and IEC 60754-1
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2, UL VW-1, CSA FT1 and FT2
Oil resistance:	very good - TMPU acc. to DIN VDE 0282 part 10 + HD 22.10
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Continuous flexibility:	very good
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/28

item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft	item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft	item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft
▶ 20 AWG (≈ 28/34) • 0.50 mm²					▶ 19 AWG (≈ 42/34) • 0.75 mm²					▶ 18 AWG (≈ 56/34) • 1.00 mm²				
77842003	3	0.339	8.6	58	77841903	3	0.354	9.0	65	77841803	3	0.362	9.2	71
77842004	4	0.354	9.0	66	77841904	4	0.374	9.5	74	77841804	4	0.386	9.8	82
77842005	5	0.382	9.7	75	77841905	5	0.406	10.3	85	77841805	5	0.413	10.5	95
77842007	7	0.425	10.8	92	77841907	7	0.461	11.7	116	77841807	7	0.476	12.1	129
77842012	12	0.496	12.6	137	77841912	12	0.543	13.8	171	77841812	12	0.559	14.2	201
77842018	18	0.579	14.7	192	77841918	18	0.630	16.0	238	77841818	18	0.634	16.1	269
77842025	25	0.673	17.1	255	77841925	25	0.736	18.7	306	77841825	25	0.760	19.3	350
77842030	30	0.709	18.0	292	77841930	30	0.748	19.0	351	77841830	30	0.776	19.7	405
77842036	36	0.756	19.2	335	77841936	36	0.803	20.4	403	77841836	36	0.898	22.8	521


Continued on next page

also available
with blue, red and
white conductors

CONTINUOUS FLEX CABLES



S 980 CP High speed continuous flex shielded heavy duty halogen free polyurethane control cable



Marking for S 980 CP 77840715: SAB BRÖCKSKES · D-VIERSEN · 77840715 7 x 1,5 mm² S 980 CP 16 AWG/7c 77841607
 AWM Style 21060 80°C 600V CSA AWM I/II A/B 80°C 600V FT1 FT2 CE

S 980 CP is a continuous flex shielded multi-conductor 80°C, 600 V cable designed specifically for the most stressful ultra high speed applications requiring a very small bending radius. The unique design allows this cable to excel in applications where ordinary flexing cables fail. The halogen free polyurethane jacket cable with black numbered conductors passes the stringent VDE test 0282 part 10 and HD 22.10 oil test and provides excellent resistance to chemicals and abrasion. An overall tinned copper shield is recommended whenever electrical interference distorts signal transmission, or when EMI emissions need to be suppressed.

B
32

Construction:

Conductor:	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 6
Insulation:	TPE
Color code:	black conductors with consecutive numbers acc. to EN 50334; green-yellow earth wire from 3 conductors
Stranding:	specially adjusted layering with netting tape over each layer
Inner jacket:	special SABIX®
Wrapping:	netting tape
Screen:	tinned copper braiding
Wrapping:	non-woven tape
Jacket material:	TMPU acc. to DIN VDE 0282 part 10 + HD 22.10 with mat surface
Jacket color:	gray

Outstanding features:

- ▶ **labs uncritical**
(labs = enamel moisturing interfering substances)
- ▶ **flexible at low temperatures**
- ▶ **travel > 10 m is possible**
- ▶ **good EMC characteristics**
- ▶ **high abrasion resistance**

Technical data:

Nominal voltage:	DIN VDE: U ₀ /U 300/500 V UL/CSA: 600 V
Testing voltage U:	3000 V acc. to DIN VDE 0281 part 2 + HD 21.2 conductor/screen 2000 V
Min. bending radius continuous flexing:	7.5 x O.D.
Radiation resistance:	5 x 10 ⁷ cJ/kg
Temperature range static:	DIN VDE -50/+90°C flexing: -40/+90°C
Zero halogen:	acc. to DIN VDE 0472 part 815 and IEC 60754-1
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2, UL VW-1, CSA FT1 and FT2
Oil resistance:	very good - TMPU acc. to DIN VDE 0282 part 10 + HD 22.10
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Continuous flexibility:	very good
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/28

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈ lbs/mft
▶ 16 AWG (≈ 84/34) • 1.50 mm ²				
77841603	3	0.374	9.5	80
77841604	4	0.425	10.8	102
77841605	5	0.453	11.5	127
77841607	7	0.520	13.2	168
77841612	12	0.618	15.7	258
77841618	18	0.709	18.0	346
77841625	25	0.909	23.1	521
77841630	30	0.925	23.5	581
77841636	36	0.980	24.9	675

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈ lbs/mft
▶ 14 AWG (≈ 140/34) • 2.50 mm ²				
77841403	3	0.449	11.4	123
77841404	4	0.476	12.1	146
77841405	5	0.528	13.4	175
77841407	7	0.610	15.5	248
77841412	12	0.736	18.7	376
77841418	18	0.921	23.4	566
77841425	25	1.071	27.2	725
▶ 12 AWG (≈ 224/34) • 4.00 mm ²				
77841203	3	0.496	12.6	167
77841204	4	0.543	13.8	205
77841205	5	0.598	15.2	251

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈ lbs/mft
▶ 10 AWG (≈ 186/32) • 6.00 mm ²				
77841003	3	0.579	14.7	235
77841004	4	0.622	15.8	294
77841005	5	0.681	17.3	334
▶ 8 AWG (≈ 320/32) • 10.00 mm ²				
77840803	3	0.740	18.8	372
77840804	4	0.807	20.5	458
77840805	5	0.957	24.3	607
▶ 6 AWG (≈ 504/32) • 16.00 mm ²				
77840603	3	0.878	22.3	528
77840604	4	0.992	25.2	703
77840605	5	1.110	28.2	845
▶ 4 AWG (≈ 760/32) • 25.00 mm ²				
77840404	4	1.169	29.7	1011
77840405	5	1.283	32.6	1211
▶ 2 AWG (≈ 1083/32) • 35.00 mm ²				
77840204	4	1.307	33.2	1289
77840205	5	1.437	36.5	1545

Other dimensions and colors are possible on request.

E-mail: info@sabcable.com



Web site: www.sabcable.com